

TERMOKIR PL 181

Fine smoothing layer



Color

White, Gray

Packaging and Weight

Bag, 25 kg

Number of Bags per Pallet

60 units



Standards and Certifications

Meets the requirements of Israeli Standard 1920 for cement plaster

Suitable for the requirements of Israeli Standard 1414 for thermal plaster systems and Israeli Standard 5075 for safe rooms.

Green Label certified

The product has undergone Life Cycle Analysis (LCA).

It holds a verified Environmental Product Declaration (EPD).

Property and main uses

- For smoothing concrete walls, concrete blocks, autoclaved aerated concrete blocks, pumice blocks,
- Ceramic blocks, and silicate blocks.
- Serves as a final layer for plaster.
- Acts as a fine preparation layer for paint.
- Prevents water penetration.
- Suitable for indoor and outdoor use.
- Mixture ready to use, just add water.

Product Composition

Cement, graded aggregates, resins, and special additives.



Termokir Industries (1980) Ltd. | Horshim 4586500 | www.termokir.co.il

Phone +972-3-9386300 | Fax +972-3-6333498 | info@termokir.co.il

a diamond mark company

BUILDING RIGHT

Typical Consumption

Approximately 1.1 kg/m² at 1 mm thickness. Consumption may vary depending on substrate conditions and application method.

Background and Substrate

- Plaster, concrete, concrete block, aerated concrete block, pumice block, ceramic block, and silicate block.
- One day before application: Wash the surface with water to remove dust, salts, oils, or any factors that may cause an execution failure.

Technical Data

Working time	Approximately two hours
Capillary Absorption Coefficient	$K < 1.0 \text{ Kg/m}^2\text{h}^{0.5}$
Tensile Adhesion Strength after 28 days in laboratory conditions	More than 0.3 MPa
Compressive Strength after 28 days in laboratory conditions	More than 2.0 MPa

*Data refers to laboratory conditions at 23°C ± 2°C and 50% ± 5% relative humidity.

Application

Mixture preparation

- Pour 10.0-10.5 liters of clean water into a suitable and clean container, free of material residues, according to the type and speed of the electric mixer.
- Gradually add the entire contents of the bag and mix until a smooth, fine, lump-free paste is obtained.
- After waiting for about 5 minutes, mix again briefly.
- At this stage, the material is ready for use.

Despite the values above, water quantity may vary. In any case, ensure the pot life level is appropriate for the product.

It is recommended to consult with the technical department.

Method of application

- Apply a thin, compacted layer to the substrate using a smooth trowel, at the required thickness to cover the surface. After full drying, apply an additional layer and smooth using a damp sponge and smooth trowel.
- Total application thickness: 1-3 mm.

Curing

Begin curing the day after completion of the work, by moistening the layer with water for 3 consecutive days, 3 times a day. In areas with rapid drying, begin curing on the same day as application.

General instructions

- Store the product in a shaded, well-ventilated area.
- The material is suitable for use up to 9 months from the production date, provided it is stored in its original packaging under recommended conditions.
- Storage alongside gypsum-containing materials/products is strictly prohibited.
- Permitted application temperature range: 5°C - 35°C.
- This product must not be applied in systems containing gypsum-based materials without prior consultation with company representatives.
- Working time (Pot life) time may vary depending on environmental conditions at the time of application.
- Do not apply under extreme climatic conditions (dry heatwave, rain, winds).
- Dried mixture must not be reused.
- Ensure compliance with relevant standards.
- Before starting work, the company's representative must be summoned for on-site guidance.
- Since the material is alkaline, proper protection for skin and eyes is required. In case of contact, rinse immediately with running water.

Warning

It is strictly prohibited to touch and/or add other materials, including gypsum and/or gypsum-containing products, to this product.

Warranty

The company's responsibility is limited to the standard and quality of materials only and does not supersede the operator's responsibility. The worker must check the product and system's suitability for their needs, compatibility with other materials, and proper execution of the work. We reserve the right to update or change the data and recommendations without advance notice. The worker is responsible for checking the latest updates.

Translation Disclaimer

This product information has been translated from Hebrew to English for convenience only. In case of any discrepancy between the English translation and the original Hebrew language, the Hebrew version shall prevail. Therefore, we recommend relying solely on the information written in Hebrew! Furthermore, before using any product, you should consult the technical department for prior advice and support during use. The company accepts no responsibility for any damage or loss resulting from failure to comply with these instructions.

Updated: 11.2025