



## SAKRET PR 002

### Primer for Silicone Sealing



#### Color

Transparent

#### Packaging and Weight

Can, 500 mL

### Standards and Certifications

Work must comply with the guidelines of Israeli Standard 6551 for pools.

### Main Properties and Uses

- Primer for expansion joint filling in silicone sealing applications using SAKRET SE 963.
- Suitable for swimming pools and areas with standing water.
- Suitable as a primer before filling expansion joints in natural and artificial stone cladding.
- Provides full adhesion to the joint interior.
- Suitable for indoor and outdoor use
- Ready-to-use product, requiring no dilution.

### Material Composition

Polyurethane resin

### Typical Consumption

Approximately 125 mL/m<sup>2</sup>. Consumption may vary depending on substrate conditions and application method.

### Technical Data

Specific Gravity	Approximately 0.9 g/cm <sup>3</sup> .
Drying Time	Approximately 3 hours.

\*Data refers to laboratory conditions at 23°C ± 2°C and 50% ± 5% relative humidity



## Application Method

- Before application, remove dust, salts, and oil from the joint interior and remove any other factors that may cause execution failure.
- Apply a thin and uniform layer inside the joint using a brush of appropriate width.
- Ensure full coverage of the joint interior.
- Allow the material to dry for approximately 3 hours (or until touch-dry) before applying SAKRET SE 963.

## General Guidelines

- Store the product in a shaded, well-ventilated area.
- The material is suitable for use up to 12 months from the production date, provided it is stored in its original packaging under recommended conditions.
- Permitted application temperature range: 5°C - 35°C.
- Ensure adequate ventilation during application.
- Do not apply under extreme climatic conditions (heatwave, rain, winds)
- All work must be carried out in accordance with applicable standards.
- Before performing the work, contact the company's representatives for guidelines and a technical data sheet.
- Keep out of reach of children. In the event of skin or eye contact, rinse with plenty of water.

## Warranty

The company's warranty is limited to the integrity and quality of materials only and does not replace the worker's responsibility. The worker must check the product and system's suitability for their needs, compatibility with other materials, and proper execution of the work. We reserve the right to update or change the data and recommendations without advance notice. The worker is responsible for checking the latest updates.

## Translation Disclaimer

This product information has been translated from Hebrew to English for convenience only. In case of any discrepancy between the English translation and the original Hebrew language, the Hebrew version shall prevail. Therefore, we recommend relying solely on the information written in Hebrew! Furthermore, before using any product, you should consult the technical department for prior advice and support during use. The company accepts no responsibility for any damage or loss resulting from failure to comply with these instructions.

Updated: 11.2025