



SAKRET PR 005

Fast-Bonding Liquid Primer



Color

Purple

Packaging and Weight

Bucket, 5 liters (approximately 6.5 kg)

Main Properties and Uses

- Primer for cement-based adhesives in flooring applications.
- Especially suitable for new flooring over existing flooring (porcelain and ceramic tiles, terrazzo, natural stone, marble).
- Optimized for non-absorbent substrates.
- Contains quartz sand, enhancing adhesion strength.
- Provides full bonding to the substrate.
- Fast drying (approximately 45 minutes), depending on weather conditions.
- Ready-to-use product, requiring no dilution.

Material Composition

Acrylic emulsion, graded aggregates, and special additives.

Typical Consumption

Approximately 50 m² per bucket (100–150 g/m²). Consumption may vary depending on substrate conditions and application method.

Technical Data

Density	Approximately 1.3 kg/L.
Tensile Adhesion Strength After 6 Hours	Greater than 0.5 MPa
Tensile Adhesion Strength after 28 Days	Greater than 1.0 MPa

*Data refers to laboratory conditions at 23°C ± 2°C and 50% ± 5% relative humidity

Application Method

- Mix the primer inside the bucket before use.
- Apply using a roller, brush, or other suitable tool.
- Ensure full coverage of the substrate.
- Ensure the material is dry to the touch before applying the next layer in the system.



General Guidelines

- Store the product in a shaded, well-ventilated area.
- The material is suitable for use up to 18 months from the production date, provided it is stored in its original packaging under recommended conditions.
- Permitted application temperature range: 5°C - 35°C.
- Ensure adequate ventilation during application.
- Do not apply under extreme climatic conditions (heatwave, rain, winds)
- All work must be carried out in accordance with applicable standards.
- Before performing the work, contact the company's representatives for guidelines and a technical data sheet.
- When applying the material using methods other than a roller or brush, such as airless spraying, wear gloves and protective goggles.
- Keep out of reach of children. In the event of skin or eye contact, rinse with plenty of water.

Warranty

The company's warranty is limited to the integrity and quality of materials only and does not replace the worker's responsibility. The worker must check the product and system's suitability for their needs, compatibility with other materials, and proper execution of the work. We reserve the right to update or change the data and recommendations without advance notice. The worker is responsible for checking the latest updates.

Translation Disclaimer

This product information has been translated from Hebrew to English for convenience only. In case of any discrepancy between the English translation and the original Hebrew language, the Hebrew version shall prevail. Therefore, we recommend relying solely on the information written in Hebrew! Furthermore, before using any product, you should consult the technical department for prior advice and support during use. The company accepts no responsibility for any damage or loss resulting from failure to comply with these instructions.

Updated: 11.2025