



SAKRET SE 944

Sealing tape for wall-to-wall and floor-to-wall connections



Color
Yellow
Package Type
Box
Number of units per package
1

Standards and Certifications

Complies with the requirements of EN 1928.

Tested according to EN ISO 527-3.

Properties and main uses

- For sealing connections between walls and between floors and walls.
- For sealing connections between different substrates.
- For indoor use as part of a cladding system.
- Especially suitable for drywall substrates.
- Suitable for "wet rooms," swimming pools, and industrial kitchens.
- High elasticity.
- Resistant to acidic and alkaline environments.
- For both interior and exterior use.
- Material properties remain stable within a temperature range of -30°C to +90°C.
- Easy and convenient to use.

Material Composition

Thermoplastic elastomer coated with non-woven polypropylene.

Tape Dimensions

Length: 50 m, width: 12 cm, thickness: 0.66 mm.

Background and Substrate

Concrete, concrete blocks, pumice blocks, drywall panels.



Technical Data

Tensile strength	120 N / 15 mm
Tensile strength (transverse)	25 N / 15 mm
Elongation at break	70%
Elongation at break (transverse)	300%
Tear resistance	More than 1.5 atm
Water pressure resistance	More than 1.5 atm

*Data refers to laboratory conditions at 23°C ± 2°C and 50% ± 5% relative humidity

Application Method

- Remove dust, salts, oil, and any other substances that may compromise adhesion.
- Adhere the tape using adhesive from the "AD" line, according to the type of tile to be installed.
- In overlapping areas between tapes or between tapes and corner sheets, apply Termokir SE 980 (Elastosil).

General Instructions

- Store the product in a shaded, well-ventilated area.
- The material is suitable for use up to 24 months from the production date, provided it is stored in its original packaging under recommended conditions.
- Permitted application temperature range: 5°C - 35°C.
- Protect the material from UV radiation for several weeks after installation.
- All work must be carried out in accordance with applicable standards.
- Before starting work, the company's representative must be summoned for on-site guidance.

Warranty

The company's warranty is limited to the integrity and quality of materials only and does not replace the worker's responsibility. The worker must check the product and system's suitability for their needs, compatibility with other materials, and proper execution of the work. We reserve the right to update or change the data and recommendations without advance notice. The worker is responsible for checking the latest updates.

Translation Disclaimer

This product information has been translated from Hebrew to English for convenience only. In case of any discrepancy between the English translation and the original Hebrew language, the Hebrew version shall prevail. Therefore, we recommend relying solely on the information written in Hebrew! Furthermore, before using any product, you should consult the technical department for prior advice and support during use. The company accepts no responsibility for any damage or loss resulting from failure to comply with these instructions.

Updated: 11.2025