



## SAKRET SE 960

### Acrylic mastic for filling and sealing



Color

White

Package Type and Weight

Bucket, 25 kg

Number of buckets per pallet

14

### Standards and Certifications

Complies with the requirements of Israeli Standard 1536 and ISO 11600 for sealing materials.

Tested according to ISO 8339.

Meets the requirements of Israeli Standard 2378 Part 5 and Israeli Standard 1872 Part 5 for industrialized cladding methods ("Baranovitch").

### Properties and main uses

- For securing hooks in construction using the "Baranovitch Method."
- For sealing standard vertical joints ("0") between stone panels.
- For filling and sealing cracks in all building walls.
- Excellent adhesion to concrete, plaster, wood, aluminum, metal, etc.
- Easy and convenient to use, long-lasting flexibility, can be painted.
- Material properties remain stable within a temperature range of -25°C to +80°C.

### Material Composition

Resins and special additives.

### Typical Consumption

1.6 kg/m<sup>2</sup> at a thickness of 1 mm (consumption may vary depending on substrate conditions and application method).

### Technical data

Specific Gravity	1.6 kg/L.
Initial drying (skin formation)	About 10 minutes
Hardness according to Shore A	15-25
Movement capability	12.5%
Elastic recovery	More than 40%

\*Data refers to laboratory conditions at 23°C ± 2°C and 50% ± 5% relative humidity



## Application method

- To secure the hooks, dip the hook into the material up to the bend and install it in place.
- For filling "O" joints between adjacent tiles, apply SAKRET SE 960 using a smooth trowel or other suitable tool. Then, level the surface and allow it to dry.

**If material remains in the bucket after completing the work, cover it with a polyethylene sheet and close the bucket with its lid.**

## General instructions

- Store the product in a shaded, well-ventilated area.
- The material is suitable for use up to 12 months from the production date, provided it is stored in its original packaging under recommended conditions.
- Permitted application temperature range: 5°C - 35°C.
- The product is unsuitable for filling expansion joints between natural stone tiles.
- All work must be carried out in accordance with applicable standards.
- Workability time may vary depending on environmental conditions at the time of application.
- Do not apply under extreme climatic conditions (heatwave, rain, winds).
- Before starting work, consult company representatives for guidelines and technical specifications.
- Keep out of reach of children. In the event of skin or eye contact, rinse with plenty of water.

## Warranty

The company's warranty is limited to the integrity and quality of materials only and does not replace the worker's responsibility. The worker must check the product and system's suitability for their needs, compatibility with other materials, and proper execution of the work. We reserve the right to update or change the data and recommendations without advance notice. The worker is responsible for checking the latest updates.

## Translation Disclaimer

This product information has been translated from Hebrew to English for convenience only. In case of any discrepancy between the English translation and the original Hebrew language, the Hebrew version shall prevail. Therefore, we recommend relying solely on the information written in Hebrew! Furthermore, before using any product, you should consult the technical department for prior advice and support during use. The company accepts no responsibility for any damage or loss resulting from failure to comply with these instructions.

Updated: 11.2025