



# EPD

Environmental  
Product  
Declaration

In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

## Termokir Flooring Materials (FL Series)



### Termokir FL 820 Gray

Enhanced cement mortar for  
tiles flooring

Programme: The International EPD® System  
[www.environdec.com](http://www.environdec.com)

Programme operator: EPD International AB

EPD registration number: S-P-11956

Publication date: 2023-12-29

Valid until: 2028-12-29



An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at [www.environdec.com](http://www.environdec.com)

# General information



|                         |                                                                  |
|-------------------------|------------------------------------------------------------------|
| Programme               | The International EPD® System                                    |
| Programme Operator      | EPD International AB                                             |
| EPD registration number | S-P-11956                                                        |
| Date of publication     | 2023-12-29                                                       |
| Date of validity        | 2028-12-29                                                       |
| Website                 | <a href="http://www.environdec.com">www.environdec.com</a>       |
| email                   | <a href="mailto:info@environdec.com">info@environdec.com</a>     |
| Address                 | EPD International AB, Box 210 60,<br>SE-100 31 Stockholm, Sweden |

## Accountabilities for PCR, LCA and independent, third-party verification

### Product Category Rules (PCR)

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product Category Rules (PCR): PCR 2019:14 Construction products (EN 15804:A2) (1.2.5) published by the International EPD® System

PCR review was conducted by: The Technical Committee of the International EPD® System. See [www.environdec.com/TC](http://www.environdec.com/TC) for a list of members. Review chair: Claudia A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat [www.environdec.com/contact](http://www.environdec.com/contact).

### Life Cycle Assessment (LCA)

LCA accountability: Shira Shabtai, Sher Consulting and Training Ltd.

### Third-party verification

Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:

EPD® verification by individual verifier

Third-party verifier: Itxaso Trabudua, IK Ingeniería S.L., [i.trabudua@ik-ingenieria.com](mailto:i.trabudua@ik-ingenieria.com)

Approved by: The International EPD® System

Procedure for follow-up of data during EPD validity involves third party verifier:

☒ Yes    ☐ No



|                  |                                                                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EPD Owner        | Termokir Industries Ltd.<br>Contact: Dr. Semeon Fraimovich<br>Phone: +972-3-9386305<br>E-mail: <a href="mailto:semeonf@termokir.co.il">semeonf@termokir.co.il</a><br>Website: <a href="http://www.termokir.co.il">www.termokir.co.il</a> |
| LCA practitioner | The LCA was performed by Sher Consulting and Training Ltd.<br>12 Habazelet st, Tzur Yigal, Israel, 4486200<br>Phone: +972-9-7492232<br>E-mail: Admin@2sher.co.il<br>Website: <a href="http://www.2sher.com">www.2sher.com</a>            |

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmers may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.



# Company information

## About the Company



Established in 1983, Termokir Industries Ltd. (1980) is a kibbutz-owned company based in Kibbutz Horshim providing innovative construction and building solutions for the Israeli market. Termokir supplies more than 50 different mortar products, providing high-quality technological solutions based on sustainability principles and designed for building claddings, floorings, adhesion, sealing, insulation and acoustics applications, as well as for concrete repair and grout products. All of the company's products are manufactured on the grounds of the Kibbutz.

## Company Strategy

Over the years, Termokir has become a mainstay in the Israeli construction market due to the company's clear value proposition based on three main strategic anchors: Technology - developing innovative and environmentally-minded products tailored to the local construction industry; Quality – putting our stakeholders first by developing high-quality solutions based on international standards and certification frameworks, while also providing related services and training, and thorough technical guidance in implementation of the company's systems and products; and Sustainability – the anchor at the core of the company's value proposition, beginning with the development of its first "Thermal Plaster" product recognized for its contribution to building energy savings and efficiency in construction. The company continues to develop environmental products and to operate its factory and manufacturing processes in a sustainable way.

In addition, the company strives to achieve green office principles, by recycling, reusing and minimizing the use of paper, and other materials, and by encouraging the use of digital means. Finally, Termokir engages in social impact projects with the community to implement its recycling program, for example, by working with organizations that employ individuals with disabilities.

Through the implementation of these anchors, Termokir strives to continuously challenge, improve and be innovative in the Israeli construction market.



### **Product-related or management system-related certifications:**

Termokir's manufacturing site has received the Israeli Standards Institute Diamond mark which reflects a recipient company's conformity to seven Israeli and international standard quality marks related to their management systems, processes, and products. These include: ISO 9001, ISO 14001, ISO 50001, ISO 45001 and ISO 27001, the Israeli Green Label, and the Standards Mark. All are certified under the scope "Manufacture of thermal insulation plasters, industrial plasters, coating & finishing layers, glues for tiles, sealing materials, etc."

### **Name and location of production site(s)**

All data utilized for the life cycle assessment is related to the Company's production plant located in Kibbutz Horshim, Israel.



# Product information



**Product name:** Termokir FL 820 Gray - enhanced cement mortar for tiles flooring

## Product identification, description and use:

All Termokir products are manufactured in Israel in a dry mix process at the company's manufacturing site in Kibbutz Horshim. Raw materials are fed automatically from silos, additives are premixed and added automatically as a compound or added without premixing through automatic or manual addition based on the type of additive. The ready-mixed product is filled in paper bags, size depending on the intended use or application.

Termokir products contain no substances that appear in the REACH candidate list of SVHC ("Candidate list of substances of very high concern").

The Termokir FL series is intended as a mortars for tile flooring. The products are meant for internal and can be used in residential and public buildings, offices, etc. FL series is suitable for concrete substrates. All products in this series comply with the Israeli Standard 6069 and were awarded the Israeli Green Label.

The products are marketed in a paper bag as dry mix products; a mixture ready for use with water addition only. The bags are transported on wooden pallets, packaged under polyethylene film (54 x 40 kg bags per pallet for Termokir FL 820).

## Product Contents:

| Component           | FL Family |
|---------------------|-----------|
| Cement              | 20-25%    |
| Fillers             | 5-10%     |
| Aggregates          | 67-75%    |
| Special additives   | 0.5-1.5%  |
| Packaging Materials | FL Family |
| kraft paper         | 95%       |
| LDPE                | 5%        |

0.003 kg (95% kraft paper, 5% LDPE)

**UN CPC code:** 375 – Articles of concrete, cement and plaster.

# LCA information

**Functional units** (and functional units for conversion):

- 1 kg of Termokir FL 820 Gray

**Database(s) and LCA software used:** For Termokir Products components and energy requirements the data was collected directly from Termokir Ltd. The life cycle analysis (LCA) has been done according to the requirements/guidelines of ISO 14040, using specialized LCA software (SimaPro 9.5).

**Time representativeness:** The data used to model product manufacturing corresponds to 2022, the data from LCA generic databases is from 2011 – 2022.

Assessment period for each module considered in the LCA - one-year average.

**Inputs used for software:** Relevant datasets for raw materials and waste handling are not available for Israel. Therefore, all input and output streams were taken from the Ecoinvent 3.9.1 which is relevant mostly for Europe. As Israel is following EU environmental regulation very closely, we assume the results will not differ much when local data becomes available.

**Description of system boundaries and key assumptions:**


- The life cycle analysis presented is a cradle-to-gate with modules C1-C4 and module D analysis. The EPD includes the analysis of the product stage (A1-A3), End of life (C1-C4) and resource recovery stage (D). Process A1-A3 include raw material production, manufacturing of the product. Process C1-C4 represents the end-of-life treatments - transportation and landfill/ recycling treatment. D Module represents benefits from resource recovery occurring in researched scenario and beyond study boundaries. Reuse- Recovery- Recycling potential: Module D calculates the potential environmental benefits of the recycling or reuse of materials. The scenarios included are currently in use and are representative for one of the most probable.
- This study includes the transport of raw materials and packaging materials to the production site, by road or sea.



- Packaging-related flows in the production process are included in the manufacturing module (wooden pallets, paper sack and LDPE film).
- A small amount of process waste is produced that is reprocessed as filling material. A conservative assumption has been made that all the environmental impact is allocated to the product and not the co-product (i.e. the filling material). The amount of filling materials differs between the Company's products.
- Packaging waste was not included in the LCA study as it is repurposed fully (100%) and used to make bags & notebooks by 'Orange Heart' (a rehabilitation project which employs people with mental illness). The notebooks are designed by designers from the 'terminal'- a social enterprise which promotes young Israeli designers while sponsoring social and educational enterprises in the arts.
- The impact assessment method used in this study is EN 15804+A2. The impact indicators can be found below.
- Raw materials: Relevant datasets for raw materials are not available for Israel. Therefore, most datasets were taken from the Ecoinvent 3.9.1 which is relevant mostly for Europe. As Israel is following EU environmental regulation very closely, we assume the results will not differ much when local data becomes available.
- Transportation distances: Raw materials and packaging materials are imported from several countries; travel distances were calculated based on the location of manufacture, and assuming arrival via the Ashdod port, from which most of the raw materials arrive before being sent to the company's manufacturing facility.
- Transportation to waste facility treatment was modelled as 50 km, as Israel is a small country (C2).
- End of life: Beyond the transportation of waste mentioned in the paragraph earlier, the end-of-life treatment modeled is 58% recycle and 42% landfill. This is based on a report by the Israeli Knesset using the environmental protection agency data from 2021<sup>1</sup> (C3-C4).

<sup>1</sup> [https://fs.knesset.gov.il/globaldocs/MMM/4a321fa6-5669-ec11-8142-00155d0401c3/2\\_4a321fa6-5669-ec11-8142-00155d0401c3\\_11\\_19422.pdf](https://fs.knesset.gov.il/globaldocs/MMM/4a321fa6-5669-ec11-8142-00155d0401c3/2_4a321fa6-5669-ec11-8142-00155d0401c3_11_19422.pdf)

## System diagram:




## Standards

- The Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804:2012+A2:2019/AC:2021 and applicable construction products PCR 2019:14 - Version 1.2.5.
- ISO 14040/44 (International Organization for Standardization (ISO) 2006a, b).

**Allocation:** The study uses mass allocation method. Additionally, the allocation method used in this study for all data sets is the "cut off" method. Regarding end of life, this method does not include burdens of the recycling, but rather only transportation to recycling facilities, as it considers the burdens and credit of recycling to the "second" product produced from recycled material.

A small amount of process waste is produced that is reprocessed as filling material. A conservative assumption has been made that all the environmental impact is allocated to the product and not the co-product (i.e., the filling material). The amount of filling materials differs between the Company's products.

**Cut-off:** The upstream processes include extraction and processing of raw materials, primary fuels used and transportation to the facility. The core process includes all product manufacturing processes at the manufacturing facility itself. The study applies a cut-off criterion of 1%. More than 99 mass % of the materials have been included in the LCA. As some raw materials were not found in the available databases, these were cut-off after finding that the contribution from those materials was less than 1% of the product mass. Excluded processes and materials: machine oil, machine cleaners, factory cleaning.



## Declared Modules

The life cycle stages included in the analysis are illustrated in the table below, according to EN 15804. The EPD includes the analysis of the product stage (A1-A3), End of life (C1-C4) and resource recovery stage (D). If a module is included, it is indicated with “X” and if it is excluded with a “ND” (Not Declared).

|                      | Product stage       |               |               | Construction process stage |                           | Use stage |             |        |             |               |                        |                       | End of life stage          |           |                  |          | Resource recovery stage            |
|----------------------|---------------------|---------------|---------------|----------------------------|---------------------------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|------------------------------------|
|                      | Raw material supply | Transport     | Manufacturing | Transport                  | Construction installation | Use       | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-recovery recycling-potential |
| Module               | A1                  | A2            | A3            | A4                         | A5                        | B1        | B2          | B3     | B4          | B5            | B6                     | B7                    | C1                         | C2        | C3               | C4       | D                                  |
| Modules declared     | X                   | X             | X             | ND                         | ND                        | ND        | ND          | ND     | ND          | ND            | ND                     | ND                    | X                          | X         | X                | X        | X                                  |
| Geography            | IL, EU Global       | IL, EU Global | IL            | ND                         | ND                        | ND        | ND          | ND     | ND          | ND            | ND                     | ND                    | IL                         | IL        | IL               | IL       | IL                                 |
| Specific Data Used   | >90%                |               |               | -                          | -                         | -         | -           | -      | -           | -             | -                      | -                     | -                          | -         | -                | -        | -                                  |
| Variation - Products | 0%                  |               |               | -                          | -                         | -         | -           | -      | -           | -             | -                      | -                     | -                          | -         | -                | -        | -                                  |
| Variation - Sites    | 0%                  |               |               | -                          | -                         | -         | -           | -      | -           | -             | -                      | -                     | -                          | -         | -                | -        | -                                  |

**A1** Includes the raw material production, from a number of different countries (Germany, The Netherlands, Turkey, Israel, Spain, China).

**A2** Describes the shipping and transportation of these materials to Termokir facility in the state of Israel.

**A3** Includes the production of the 49 items, in Termokir facility. All Termokir products are manufactured in Israel in a dry mix process at the company's manufacturing site in Kibbutz Horshim. Raw materials are fed automatically from silos, additives are premixed and added automatically as a compound or added without premixing through automatic or manual addition based on the type of additive. The ready-mixed product is filled in paper bags, size depending on the intended use or application. The biogenic carbon content in the packaging is presented in table 4. The electricity power mix selected is Israel grid for the year 2021 based on published data from the Israeli ministry of environmental protection<sup>1</sup> - 69% natural gas, 23% coal, 8% renewable energy.

A small amount of process waste is produced that is reprocessed as filling material. A conservative assumption has been made that all the environmental impact is allocated to the product and not the co-product (i.e., the filling material). The amount of filling materials differs between the Company's products.

Packaging waste was not included in the LCA study as it is repurposed fully (100%) and used to make bags & notebooks.

Process C1-C4 represents the end-of-life treatments - transportation and landfill/ recycling treatment.

**C1** - Takes place with the whole demolition of the building. It is assumed that no significant energy is associated with Termokir items as part of the building demolition.

There for the environmental impact of this module is set to be zero.

**C2** – Transportation distances to the closest landfill and recycle plant are estimated as 50 km by 16-32 tone lorry (eur04).

**C3** - The end-of-life treatment modeled is 58% recycle and 42% landfill. This is based on a report by the Israeli Knesset using the environmental protection agency data from 2021<sup>2</sup>.

**C4** – 42% of the waste is send to landfill in the state of Israel.

**D** Module represents benefits occurring in researched scenario and beyond study boundaries - resources recovery (Reuse- Recovery-

---

<sup>1</sup> Israel Ministry of environmental protection – A review of the electricity sector in Israel

<sup>2</sup> Israel Knesset - Construction waste process in Israel

Recycling potential). Module D calculates the potential environmental benefits of the recycling or reuse of materials. The module D assumptions have not been changed (year of reference, electricity and power production, amount, quality of material and material losses). The scenarios included are currently in use and are representative for one of the most probable.

| Processes                  | Unit                                                                                                                   |
|----------------------------|------------------------------------------------------------------------------------------------------------------------|
| Collection                 | 1 kg collected with mixed construction waste                                                                           |
| Recovery                   | Recycling – 0.58 kg                                                                                                    |
| Disposal                   | 0.42 kg                                                                                                                |
| Transportation Assumptions | Transportation distances to the closest landfill and recycle plant are estimated as 50 km by 16-32 tone lorry (eur04). |

Table 2 – EOL



# Environmental Information

LCA results are detailed in the following tables.



## Termokir FL 820 Gray

### Potential environmental impact— mandatory indicators according to EN 15804

| Indicator              | Unit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | A1 - A3  | C1      | C2      | C3      | C4      | D         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------|---------|---------|---------|-----------|
| GWP-fossil             | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2.8E-01  | 0.0E+00 | 9.5E-03 | 7.1E-03 | 2.6E-03 | -3.25E-01 |
| GWP-biogenic           | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | -1.1E-02 | 0.0E+00 | 3.6E-06 | 1.1E-02 | 1.5E-06 | 4.96E-03  |
| GWP-luluc              | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 8.7E-05  | 0.0E+00 | 5.0E-06 | 4.0E-07 | 1.5E-06 | -4.10E-04 |
| GWP-total              | kg CO <sub>2</sub> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 2.7E-01  | 0.0E+00 | 9.5E-03 | 1.8E-02 | 2.6E-03 | -3.20E-01 |
| ODP                    | kg CFC 11 eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 1.8E-09  | 0.0E+00 | 1.5E-10 | 1.2E-10 | 7.4E-11 | -3.60E-09 |
| AP                     | mol H <sup>+</sup> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 9.6E-04  | 0.0E+00 | 4.2E-05 | 3.4E-05 | 1.9E-05 | -1.46E-03 |
| EP-freshwater          | kg PO <sub>4</sub> <sup>3-</sup> eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 1.3E-05  | 0.0E+00 | 2.8E-07 | 4.8E-07 | 7.7E-08 | -1.44E+00 |
| EP-freshwater          | kg P eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4.1E-06  | 0.0E+00 | 9.0E-08 | 1.5E-07 | 2.5E-08 | -4.41E+00 |
| EP-marine              | kg N eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2.6E-04  | 0.0E+00 | 1.5E-05 | 4.9E-06 | 7.4E-06 | -3.34E-04 |
| EP-terrestrial         | mol N eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 2.8E-03  | 0.0E+00 | 1.6E-04 | 5.4E-05 | 8.0E-05 | -3.57E-03 |
| POCP                   | kg NMVOC eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 8.5E-04  | 0.0E+00 | 5.6E-05 | 2.1E-05 | 2.8E-05 | -1.10E-03 |
| ADP-minerals & metals* | kg Sb eq.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 8.1E-07  | 0.0E+00 | 3.1E-08 | 6.6E-09 | 3.6E-09 | -1.08E-06 |
| ADP-fossil*            | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 2.4E+00  | 0.0E+00 | 1.3E-01 | 9.5E-02 | 6.4E-02 | -3.98E+00 |
| WDP                    | m <sup>3</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 5.0E-01  | 0.0E+00 | 6.0E-04 | 3.4E-04 | 2.8E-03 | -5.59E-02 |
| Acronyms               | GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption |          |         |         |         |         |           |

\* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

## Potential environmental impact – additional mandatory indicator

| Indicator            | Unit                   | A1-A3   | C1      | C2      | C3      | C4      | D         |
|----------------------|------------------------|---------|---------|---------|---------|---------|-----------|
| GWP-GHG <sup>1</sup> | kg CO <sub>2</sub> eq. | 2.8E-01 | 0.0E+00 | 9.7E-03 | 7.2E-03 | 2.7E-03 | -3.26E-01 |

## Use of resources

| Indicator | Unit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | A1-A3    | C1      | C2      | C3      | C4      | D         |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------|---------|---------|---------|-----------|
| PERE      | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2.1E-01  | 0.0E+00 | 1.7E-03 | 2.0E-03 | 5.4E-04 | -4.61E-01 |
| PERM      | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 4.02E-02 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00   |
| PERT      | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2.5E-01  | 0.0E+00 | 1.7E-03 | 2.0E-03 | 5.4E-04 | -4.61E-01 |
| PENRE     | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2.4E+00  | 0.0E+00 | 1.3E-01 | 9.5E-02 | 6.4E-02 | -3.98E+00 |
| PENRM     | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 6.37E-03 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00   |
| PENRT     | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2.4E+00  | 0.0E+00 | 1.3E-01 | 9.5E-02 | 6.4E-02 | -3.98E+00 |
| SM        | kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.0E+00  | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00   |
| RSF       | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.0E+00  | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00   |
| NRSF      | MJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.0E+00  | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00 | 0.0E+00   |
| FW        | m <sup>3</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1.2E-02  | 0.0E+00 | 1.9E-05 | 1.2E-05 | 6.8E-05 | -1.87E-03 |
| Acronyms  | PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water |          |         |         |         |         |           |

## Information on biogenic carbon content

The packaging total weight – 0.003 kg (95% kraft paper, 5% LDPE)

| Results per functional or declared unit |      |          |
|-----------------------------------------|------|----------|
| Biogenic Carbon Content                 | Unit | Quantity |
| Biogenic carbon content in product      | kg C | 0        |
| Biogenic carbon content in packaging    | kg C | 0.001    |

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO<sub>2</sub>.

<sup>1</sup> The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.

## Indicators describing waste

| Indicator                    | Unit | A1-A3    | C1       | C2       | C3       | C4       | D         |
|------------------------------|------|----------|----------|----------|----------|----------|-----------|
| Hazardous waste disposed     | kg.  | 6.25E-06 | 0.00E+00 | 8.73E-07 | 3.19E-07 | 3.39E-07 | -1.08E-05 |
| Non-hazardous waste disposed | kg.  | 2.33E-02 | 0.00E+00 | 6.56E-03 | 2.85E-04 | 4.22E-01 | -3.45E-02 |
| Radioactive waste disposed   | kg.  | 1.24E-06 | 0.00E+00 | 2.73E-08 | 2.04E-09 | 9.44E-09 | -6.13E-06 |

## Indicators describing output flows

| Parameter                    | Unit | A1-A3 | C1 | C2 | C3   | C4 |
|------------------------------|------|-------|----|----|------|----|
| Components for reuse         | kg   | 0     | 0  | 0  | 0    | 0  |
| Material for recycling       | kg   | 0     | 0  | 0  | 0.58 | 0  |
| Material for energy recovery | kg   | 0     | 0  | 0  | 0    | 0  |
| Exported energy, electricity | MJ   | 0     | 0  | 0  | 0    | 0  |
| Exported energy, thermal     | MJ   | 0     | 0  | 0  | 0    | 0  |

# References

- ◆ General programme instructions of the International EPD® System. Version 4.0
- ◆ PCR 2019:14 Construction products (EN 15804:A2) (1.2.5)
- ◆ EN 15804:2019 Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products
- ◆ ISO 14025: Environmental labels and declarations – type III Environmental declarations principles and procedure (2009)
- ◆ ISO 14040:2006 Environmental management - Life cycle assessment - Principles and framework
- ◆ ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines
- ◆ Termokir product declaration catalog for construction products
- ◆ SimaPro 9.5 Software and database

# Contact Information

Programme Operator



ENVIRONMENTAL PRODUCT DECLARATIONS

EPD International AB  
info@environdec.com  
www.environdec.com

EPD Owner



Termokir Industries Ltd  
www.termokir.co.il  
termokir@termokir.co.il  
Israel

LCA Author



Sher Consulting and Training Ltd.  
www.2sher.com

3rd Party Verifier



<https://www.ik-ingenieria.com/> IK Ingeniería S.L.  
i.trabudua@ik-ingenieria.com